## **World Sailing Offshore Special Regulations**

## **Inspection Card for Race Category 4 Multihulls**

- **PERSON IN CHARGE** (see Racing Rules of Sailing 46): please prepare the boat, initial above the underline and sign where indicated.
- **INSPECTORS** mark each inspected item with a checkmark or cross. Note any deficiencies on the Deficiency Report. Show the Deficiency Report to the Person in Charge, then return the report to the Race Committee as soon as possible.

Boat	
Serial number	
No of persons on board	
Disclaimer of Liability	The inspection is carried out as a courtesy. An inspector cannot limit or reduce the complete and unlimited responsibility of the owner and the person in charge.  "I hereby declare that I am the Person in Charge, that wherever I initial an item on this checklist it conforms to its associated Offshore Special Regulation (OSR), that I have read and understand the OSRs and in particular 1.02.1 and 1.02.2
Printed name	
Signed	
Date	
	JANUARY 2016- DECEMBER 2017 including updates January 2017 © ORC Ltd. 2002, amendments 2003-2017 © World Sailing Limited  Version 0.3 - 03 March 2017
	Lay out on Chart Table or other Surface
4.11.1	Charts (not solely electronic ), light list, plotting equipment
	Lay out on Bunk(s)
3.29.05	1 watertight handheld VHF radio transceivers stowed in grab bag
3.29.06	2nd radio capable of receiving weather, could be the handheld VHF
4.08.1	First Aid Manual and First Aid Kit

4.09.1	Foghorn
4.16.1 4.23.1	Tools, spare parts, method to disconnect/sever standing rigging  List all flare expiry dates
5.01.1	Lifejacket with light, whistle etc, 1 for each crew, marked with name
5.01.1 a)i)	Each lifejacket has crotch or thigh straps
5.01.4	Each lifejacket inspected by person in charge, within last 12 months
3.07.1	Below Deck Inspection At least 2 exits in each hull which contains accommodation if LH greater than 8m
3.07.2 b)	At least 2 escape hatches in each hull which contains accommodation
3.08.2	Portlights that open inward labelled "NOT TO BE OPENED AT SEA"
3.10.1	Sea cocks or valves on through-hull openings below waterline
3.12.1	Heel of keel-stepped mast is secured to structure
3.13.1	Crash bulkhead
3.18.2	Toilet or fitted bucket, permanently installed
3.19.2	Bunks, permanently installed
3.22.1	Handholds below deck
3.27.4	Spare bulbs for navigation lights (not required for LED)
4.03.1	Tapered soft wood plug at each through-hull fitting
4.05.1	A fire blanket adjacent to every cooking device with an open flame
4.05.2	2 fire extinguishers, in different parts of the boat
4.12.1	Safety equipment location chart
	At Helm, Ready for Rapid Deployment
4.22.3	Lifebuoy with self-igniting light and drogue
4.22.7	Heaving line min.6mm, 15-25m

On Deck, Where Stowed or Ready for Deployment

3.08.4 b) ii	Hatch blocking devices attached and can be secured in place
4.25.1	A strong, sharp knife, sheathed and securely restrained
	Rigged/Fitted to Demonstrate Use
3.27.1	Navigation lights, above sheerline and not obscured when sailing
4.10.1	Radar reflector
4.10.1 a)	Radar target enhancer
4.26.1 c)	Sheeting positions for each heavy/storm sail
	General
2.04.1	All equipment is readily available, adequately sized and functions
2.04.2	Heavy items are permanently installed or securely fastened
3.01.1	The boat is strongly built, seaworthy and watertight
3.05.2	Transverse watertight bulkheads max 4m spacing in non-accommodation hulls
3.07.2 d)	Handholds and clipping points on underside of boat
3.08.1	Forward hatches open outward only
3.08.3	Hatches are attached, above water at 90° heel & operable if capsized
3.09.1	Cockpit is strong , watertight and meets OSR size and drainage
3.14.1	Double lifelines & pulpits, surround entire deck, 600mm high
3.23.1 a)	2 strong buckets, each with lanyard and 9 litre min capacity
3.23.2	Permanently installed manual bilge pump operable with all hatches closed
3.23.1 c)	Provision to pump out all watertight compartments (excluding foam-filled)
3.23.3	Bilge pump neither connects to cockpit drains nor discharges into cockpit
3.24 a)	2nd magnetic compass, may be hand-held and/or electronic
3.25	No less than 2 halyards per mast, each capable of hoisting a sail
4.01.1	Sail letters and numbers meeting RRS 77
4.17.1	Boat's name on buoyant equipment